

UNIVERSAL SINGLE-SIDED HIGH-ADHESIVE TAPE

- Universal tape with excellent initial tack and superior adhesion strength on any surface. It can be used both indoors and outdoors
- Guaranteed adhesion over time even at low temperatures and on dusty, porous or damp surfaces
- Available in various sizes, also with pre-cut liner, for easy installation even in complex corners and edges



CODE	liner [mm]	B [mm]	L [m]	pcs
SIGNO60	60	60	25	10
SIGNO5050	50 / 50	100	25	6
SIGNO7575	75 / 75	150	25	4

Thickness: 0,34 mm

COMPOSITION

- 1 support: PE film
- 2 glue: acrylic dispersion without solvents
- 3 reinforcing layer: polyester reinforcing grid
- 4 glue: acrylic dispersion without solvents
- 5 release liner: silicone paper

TECHNICAL DATA

properties	standard	value
thickness	DIN EN 1942	0,34 mm
tear strength	DIN EN 14410	≥ 50 N/25 mm
expansion capacity	DIN EN 14410	20%
adhesiveness	EN 1939	≥ 30 N/25 mm
water vapour transmission (Sd)	EN 1931	approx. 45 m
	ASTM E96 (dry cup)	6,27 ng/(m ² ·24h) 0.11 US perm
UV resistance	-	6 months
application temperature	-	-10 / +40 °C
thermal resistance	-	-40 / +80 °C
storage temperature ⁽¹⁾	-	+5 / +25 °C
VOC emissions	EN 16000	23 µg/m ³
EMICODE	GEV test procedure	EC1 ^{PLUS}

⁽¹⁾Store the product in a dry, covered location.

