

EVERBUILD WOOD FILLER HARDENER / CATALYST

Colour	Product Code	Pack Size	Box Qty
-	WFCATALYST	40GRM	25

Product Description

EVERBUILD WOOD FILLER HARDENER is a Benzoyl Peroxide catalyst paste for use with two part styrene based wood filler systems.

Benefits

- Works with most common 2 part wood filler systems.
- Available as loose tubes.

Limitations

- Always replace cap after use.
- Do not use with single part/acrylic based systems.
- It is users responsibility to determine suitability for use. If in doubt contact technical services for advice.

Application

Remove cap and gently squeeze tube. A line of approx 38mm is sufficient to catalyse a golf ball size amount of wood filler paste. Mix two components thoroughly into a smooth uniform coloured paste.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool dry conditions away from direct sunlight between 5 and 20°C. Store in original containers and out of reach of children. Dispose of product and packaging correctly.

Shelf Life

24 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.